



















TYPE: Ranger
 MODEL: PX / T6 / T7 (3" Lift)
 YEAR: 08/2011 on
 DETAIL: Pickup/Style Side/Ranger T6 South Africa,
 Well Back/Tray Back,
 75mm (3" Lift) Also Suits 4x2 Highrider



FRONT		QTY	PART NUMBER	PRICE	REAR		QTY	PART NUMBER	PRICE
COIL SPRING					PARABOLIC LEAF SPRING				
All 2.2L Engines & 4x2 Highrider					3 + 1 Leaves Raised Height (60mm Lift)				
	Linear Rate Raised Height (3" Lift)	1	C19-442	B		2	L19-135-RP		
All 3.2L Engine 4x4s					3 + 1 Leaves Raised Height (3" Lift)				
	Linear Rate Raised Height (3" Lift) No Accessories	1	C19-458	B		2	L19-139-RP		
	Linear Rate Raised Height (3" Lift) 50-100Kg Accessories	1	C19-476	B	TAILSHAFT SPACER KIT				
SHOCK ABSORBER					Tailshaft Centre Bearing Spacer Kit 1 WA19-526K				
	Twin Tube Gas Heavy Duty	2	GS19-092		<i>Helps to Reduce Driveline Vibration in Lifted Vehicles</i>				
	Internal Monotube Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	IMS19-50092		SHACKLE BUSH KIT				
<i>X - Centre of Eye to Spring Seat</i>					Kit Contains: 2 x PB19-1523 4 x PB19-1524 4 x PB19-1525 1 PB19-1104K				
	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	MR19-50092		U-BOLT KIT				
<i>X - Centre of Eye to Spring Seat</i>					Kit Contains: 2 x UB21-466 2 UB21-466K				
SHOCK ABSORBER BRACKET					SHOCK ABSORBER				
Recommended For Optimal Remote Reservoir Positioning And Fitment 1 RM19-002									
<i>Only For Use With MR19-50092</i>					Twin Tube Gas Heavy Duty 2 GS19-081T				
STRUT CAP									
	Strut Top Cap	2	SC19-009		Internal Monotube Heavy Duty 2 IMS19-50081T				
UPPER CONTROL ARM									
(Pair) 3° Castor Built In Rubber Bushes Ball Joint Not Included 1 UCA19-004K					Monotube Remote Reservoir Heavy Duty 2 MR19-50081T				
					SHACKLE				
									
					Greasable: Fit in Pairs 2 SK19-058				
					PIN				
									
					Greasable: Fit in Pairs 2 SP59-060				
					WARNING - LIFTS EXCEEDING 50MM (2")				
					The suspension components listed on this page are for off-road use only.				
					 <ul style="list-style-type: none"> - Refer to Local Laws before Fitting to Registered/Road Vehicles - An Engineering Certificate may be required - Handling Characteristics will Diminish on Lifts Above 50mm (2") 				
					The following modifications (but not limited to) need to be made to the vehicle before the kit is fitted.				
					 <ul style="list-style-type: none"> - Adjustable Panhard Rods - Modified Leading/Trailing Arms - Brake Hoses - Extended Bump Stops - Gear Box & Drive Line Modifications - Steering Arms - Swaybar Modification 				
					Dobinsons Spring & Suspension do not accept any responsibility for injury caused to person or property through the use of the products listed on this page.				
					These products do not come with any warranty or guarantee.				