

















**TYPE:** Ranger  
**MODEL:** PX / T6  
**YEAR:** 08/2011 on  
**DETAIL:** Pickup/Style Side/Ranger T6 South Africa  
 Well Back/Tray Back  
 75mm (3" Lift) Also Suits 4x2 Highrider



FRONT			REAR		
QTY	PART NUMBER	PRICE	QTY	PART NUMBER	PRICE
<b>COIL SPRING</b>					
<b>All 2.2L Engines &amp; 4x2 Highrider</b>					
	Linear Rate Raised Height (3" Lift)	1	<b>C19-442</b>	B	
<b>All 3.2L Engine 4x4s</b>					
	Linear Rate Raised Height (3" Lift) No Accessories	1	<b>C19-458</b>	B	
	Linear Rate Raised Height (3" Lift) 50-100Kg Accessories	1	<b>C19-476</b>	B	
<b>SHOCK ABSORBER</b>					
	Heavy Duty Twin Tube Gas Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm/7.48"	2	<b>GS19-092</b>		
	X = Centre of Eye to Spring Seat	2	<b>MR19-50092</b>		
<b>STRUT CAP</b>					
	Strut Top Caps	2	<b>SC19-009</b>		
<b>PARABOLIC LEAF SPRING</b>					
	3 + 1 Leaves Raised Height (60mm Lift)	2	<b>L19-135-RP</b>		
	3 + 1 Leaves Raised Height (3" Lift)	2	<b>L19-139-RP</b>		
<b>TAILSHAFT SPACER KIT</b>					
	Tailshaft Centre Bearing Spacer Kit Helps to Reduce Driveline Vibration in Lifted Vehicles	1	<b>WA19-526K</b>		
<b>SHACKLE BUSH KIT</b>					
	Kit Contains: 2 x PB19-1523 4 x PB19-1524 4 x PB19-1525	1	<b>PB19-1104K</b>		
<b>U-BOLT KIT</b>					
	Kit Contains: 2 x UB21-466	2	<b>UB21-466K</b>		
<b>SHOCK ABSORBER</b>					
	Heavy Duty Twin Tube Gas	2	<b>GS19-081T</b>		
	Monotube Remote Reservoir Shock Heavy Duty	2	<b>MR19-50081T</b>		
<b>SHACKLE</b>					
	Greasable: Fit in Pairs	2	<b>SK19-058</b>		
<b>PIN</b>					
	Greasable: Fit in Pairs	2	<b>SP59-060</b>		
<b>WARNING - LIFTS EXCEEDING 50MM (2")</b>					
The suspension components listed on this page are for off-road use only.					
	<ul style="list-style-type: none"> <li>- Refer to Local Laws before Fitting to Registered/Road Vehicles</li> <li>- An Engineering Certificate may be required</li> <li>- Handling Characteristics will Diminish on Lifts Above 50mm (2")</li> </ul>				
The following modifications (but not limited to) need to be made to the vehicle before the kit is fitted.					
	<ul style="list-style-type: none"> <li>- Diff Drop Kits</li> <li>- Upper Control Arms</li> <li>- Brake Hoses</li> <li>- Extended Bump Stops</li> <li>- Gear Box &amp; Drive Line Modifications</li> <li>- Steering Arms</li> <li>- Swaybar Modification</li> </ul>				
Dobinsons Spring & Suspension do not accept any responsibility for injury caused to person or property through the use of the products listed on this page.					
These products do not come with any warranty or guarantee.					