

4x4




















HOLDEN - GM - ISUZU

ISUZU-51



TYPE: D-Max 2nd Gen
 MODEL: TFS85
 YEAR: 05/2012 on
 DETAIL: V-CROSS, 3.0L Turbo Diesel Single Cab/Dual Cab



FRONT		QTY	PART NUMBER	PRICE	REAR		QTY	PART NUMBER	PRICE
COIL SPRING					LEAF SPRING				
	Linear Rate Raised Height (20mm Lift) No Accessories	1	C59-134	B		2 + 1 Parabolic Raised Height (50mm Lift) Up to 70Kg Constant Load Comfort Option	2	L21-182-RP	
	Linear Rate Raised Height (40mm Lift) Up to 60Kg Accessories	1	C59-296	B		3 + 3 Leaves Medium Duty Raised Height (40mm Lift) Up to 100Kg Constant Load	2	L21-140-R	
	Linear Rate Raised Height (40mm Lift) 70-120Kg Accessories	1	C59-300	B		4 + 3 Leaves Heavy Duty Raised Height (40mm Lift) 250Kg Constant Load (Recommended)	2	L21-141-R	
SHOCK ABSORBER					SHACKLE BUSH KIT				
	Twin Tube Gas Heavy Duty	2	GS21-470			Kit Contains: 2 x PB59-1503 4 x PB59-1530 4 x PB59-1532	1	PB21-1105K	
	Internal Monotube Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	IMS21-50470		U-BOLT KIT				
X - Centre of Eye to Spring Seat						Suits L21-140-R Kit Contains: 2 x UB59-453-2	2	UB59-453-2K	
	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	MR21-50470			Suits L21-141-R Kit Contains: 2 x UB59-453-2	2	UB59-453-2K	
X - Centre of Eye to Spring Seat						Suits L21-142-R Kit Contains: 2 x UB59-437	2	UB59-437K	
STRUT CAP					SHOCK ABSORBER				
	Strut Top Cap	2	SC59-002			Twin Tube Gas Heavy Duty	2	GS43-801	
DIFF DROP						Internal Monotube Heavy Duty	2	IMS21-50471	
Diff Drop Kit						Monotube Remote Reservoir Heavy Duty	2	MR43-50801	
Decreases CV Angle					SHACKLE				
						Greasable: Fit in Pairs	2	SK21-059	
					PIN				
						Greasable: Fit in Pairs	2	SP59-060	