



TYPE: Wrangler
 MODEL: JL / JLU
 YEAR: 2018 on
 DETAIL: 2 Door, 4 Door
 50mm Lift (2")
 75mm Lift (3")







FRONT





QTY	PART NUMBER	PRICE
-----	-------------	-------

COIL SPRING



2 Door

	Linear Rate Raised Height (50mm)	1	C29-210	B
	Linear Rate Raised Height (50mm) 50-90Kg	1	C29-212	B
	Variable Rate Raised Height (75mm)	1	C29-216V	B
	Variable Rate Raised Height (75mm) 50-90Kg	1	C29-218V	B

4 Door

	Linear Rate Raised Height (50mm)	1	C29-212	B
	Linear Rate Raised Height (50mm) 50-90Kg	1	C29-214	B
	Variable Rate Raised Height (75mm)	1	C29-218V	B
	Variable Rate Raised Height (75mm) 50-90Kg	1	C29-224V	B

SHOCK ABSORBER

	Internal Monotube	2	IMS29-60736	
	Monotube Remote Reservoir (Adjustable)	2	MRA29-A736	

BUMP STOP EXTENSION

25mm Bump Stop Extension	2	BS29-566
--------------------------	---	-----------------

*Required For Clearance of 35" Tyres

CASTOR CORRECTION

Castor Corrected Lower Control Arm (Pair)	1	WA29-558K
---	---	------------------





Recommended For 50mm (2") Lift.
 Required Form 75mm (3") Lift.

REAR





QTY	PART NUMBER	PRICE
-----	-------------	-------

COIL SPRING



2 Door

	Linear Rate Raised Height (50mm)	1	C29-211	B
	Linear Rate Raised Height (50mm) 50-100Kg Constant Load	1	C29-213	
	Variable Rate Raised Height (75mm)	1	C29-217V	B
	Variable Rate Raised Height (75mm) 50-100Kg Constant Load	1	C29-219V	B

4 Door

	Linear Rate Raised Height (50mm)	1	C29-213	
	Linear Rate Raised Height (50mm) 100-200Kg Constant Load	1	C29-215	B
	Variable Rate Raised Height (75mm)	1	C29-219V	B
	Variable Rate Raised Height (75mm) 100-200Kg Constant Load	1	C29-239V	B

SHOCK ABSORBER

	Internal Monotube	2	IMS29-60737	
	Monotube Remote Reservoir (Adjustable)	2	MRA29-A737	

BUMP STOP EXTENSION

25mm Bump Stop Extension	2	BS29-567
--------------------------	---	-----------------

*Required For Clearance of 35" Tyres

SWAY BAR EXTENSION

Extended Sway Bar Link	2	SE29-569
------------------------	---	-----------------

Increases Wheel Travel For 50mm (2") Lift.
 Required For 75mm (3") Lift.