




















TYPE: BT-50
 MODEL: Series II - UP/UR
 YEAR: 10/2011 on
 DETAIL: 75mm (3") Lift 4x4 3.2L Pickup/Well
 Back /Tray Back,
 Also Suits 4x2 Highrider,



FRONT		QTY	PART NUMBER	PRICE	REAR		QTY	PART NUMBER	PRICE
COIL SPRING					LEAF SPRING				
4x2 High Rider					Leaf Spring				
	Linear Rate Raised Height (3" Lift)	1	C19-442	B		3 + 1 Leaves (Parabolic) Raised Height (60mm Lift)	2	L19-135-RP	
4x4					Leaf Spring				
	Linear Rate Raised Height (3" Lift)	1	C19-458	B		3 + 1 Leaves (Parabolic) Raised Height (3" Lift)	2	L19-139-RP	
	Linear Rate Raised Height (3" Lift) 50-100Kg	1	C19-476	B	SHOCK ABSORBER				
SHOCK ABSORBER					SHOCK ABSORBER				
	Twin Tube Gas Heavy Duty	2	GS19-092			Twin Tube Gas Heavy Duty	2	GS19-081T	
	Internal Monotube Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	IMS19-50092			Internal Monotube Heavy Duty	2	IMS19-50081T	
X - Centre of Eye to Spring Seat									
	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	MR19-50092		U-BOLT KIT				
X - Centre of Eye to Spring Seat									
SHOCK ABSORBER BRACKET					U-BOLT KIT				
Recommended For Optimal Remote Reservoir Positioning And Fitment					Kit Contains: 2 x UB21-466				
1					2				
RM19-002					UB21-466K				
Only For Use With MR19-50092					SHACKLE				
STRUT CAP									
	Strut Top Cap	2	SC19-009		Greasable: Fit in Pairs				
UPPER CONTROL ARM					2				
(Pair) 3° Castor Built In Rubber Bushes Ball Joint Not Included					SK19-058				
1					SHACKLE BUSH KIT				
UCA19-004K					Kit Contains: 2 x PB19-1523 4 x PB19-1524 4 x PB19-1525				
Must Fit When Raising Vehicle Above 50mm To Allow For Improved Caster Angle Alignment					1				
BUMP STOP					PB19-1104K				
Replacement Bump Stop Progressive Adjustable 0-25mm Extension					TAILSHAFT SPACER KIT				
2					Tailshaft Centre Bearing Spacer Kit				
BS59-560					1				
Replaces Original Bump Stop. If Exceeding Listed Spring Seat Heights This MUST Be Used To Prevent Coil Bind.					WA19-526K				
					Helps to Reduce Driveline Vibration in Lifted Vehicles				
					PIN				
									
					Greasable: Fit in Pairs				
					2				
					SP59-060				
					WARNING - 75MM (3") OR HIGHER LIFT				
					The suspension components listed on this page are for off-road use only.				
									
					- Refer to Local Laws before Fitting to Registered/Road Vehicles				
					- An Engineering Certificate may be required				
					- Handling Characteristics will Diminish on Lifts Above 50mm (2")				
					The following modifications (but not limited to) need to be made to the vehicle before the kit is fitted.				
									
					- Adjustable Panhard Rods				
					- Modified Leading/Trailing Arms				
					- Brake Hoses				
					- Extended Bump Stops				
					- Gear Box & Drive Line Modifications				
					- Steering Arms				
					- Swaybar Modification				
					Dobinsons Spring & Suspension do not accept any responsibility for injury caused to person or property through the use of the products listed on this page.				
					These products do not come with any warranty or guarantee.				