














**TYPE:** Triton, L200  
**MODEL:** MQ 5th Generation  
**YEAR:** 03/2015 on  
**DETAIL:** 4x4  
 Also Suits 4x2 Highrider



FRONT		QTY	PART NUMBER	PRICE	REAR		QTY	PART NUMBER	PRICE
<b>COIL SPRING</b>					<b>LEAF SPRING</b>				
	Linear Rate Raised Height (30mm Lift) Up to 40Kg Accessories	1	<b>C43-314</b>	B		3+2 Leaves Raised Height (30mm Lift) Comfort Option Minimal Load	2	<b>L43-163-R</b>	
	Linear Rate Raised Height (30mm Lift) 40-90Kg Accessories	1	<b>C43-316</b>	B		4+1 Leaves Raised Height (30mm Lift) Medium Duty Up to 80Kg Constant Load	2	<b>L43-162-R</b>	
Can Not Exceed 30mm Lift Due to Suspension Geometry Restrictions									
<b>SHOCK ABSORBER</b>					<b>SHACKLE BUSH KIT</b>				
** Batch Number 10250 on only, Spring Seat must not be lower than 215mm					Kit Contains: 2 x PB43-1550 4 x PB43-1551 4 x PB43-1528				
	Heavy Duty Twin Tube Gas	2	<b>GS43-800</b>				1	<b>PB43-1109K</b>	
	Internal Monotube Adjustable Spring Seat Spring Seat Height X = 215mm/8.45" **	2	<b>IMS43-50800</b>		<b>U-BOLT KIT</b>				
X - Centre of Eye to Spring Seat					Kit Contains:				
	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Spring Seat Height X = 215mm/8.45" **	2	<b>MR43-50800</b>			<b>L43-162-R</b>	2 x UB59-453-2	2	<b>UB59-453-2K</b>
X - Centre of Eye to Spring Seat					<b>L43-163-R</b>	2 x UB59-453-2	2	<b>UB59-453-2K</b>	
<b>STRUT CAP</b>					<b>L43-164-R</b>	2 x UB59-437	2	<b>UB59-437K</b>	
	Strut Top Cap	2	<b>SC43-005</b>		<b>L43-165-R</b>	2 x UB59-437	2	<b>UB59-437K</b>	
<b>TOP OUT STOP KIT</b>					<b>SHOCK ABSORBER</b>				
Top Out Stop Kit					1	<b>WA43-539K</b>			
Recommended to fit this kit with all suspension kits to maintain drop travel						Heavy Duty Twin Tube Gas	2	<b>GS43-801</b>	
					<b>SHACKLE</b>				
						Greasable: Fit in Pairs	2	<b>SK43-063</b>	
					<b>PIN</b>				
						Greasable: Fit in Pairs	2	<b>SP59-060</b>	
					<b>TAILSHAFT SPACER</b>				
					When Fitting Raised Suspension a Tailshaft Spacer is Required to Align the Centre Bearing and Prolong Life in Models with a 2 Piece Tailshaft				
					1	<b>S43-001</b>			