

4x4

















MITSUBISHI

MITS-66



TYPE: Triton, L200  
 MODEL: MQ, MR 5th Generation  
 YEAR: 03/2015 on  
 DETAIL: 4x4,  
 Also Suits 4x2 Highrider



FRONT		QTY	PART NUMBER	PRICE	REAR		QTY	PART NUMBER	PRICE
<b>COIL SPRING</b>					<b>LEAF SPRING</b>				
Can Not Exceed 30mm Lift Due to Suspension Geometry Restrictions									
	Linear Rate Raised Height (30mm Lift) Up to 40Kg Accessories	1	<b>C43-314</b>	B		3 + 2 Leaves Raised Height (30mm Lift) Comfort Option Minimal Load	2	<b>L43-163-R</b>	
	Linear Rate Raised Height (30mm Lift) 40-90Kg Accessories	1	<b>C43-316</b>	B		4 + 1 Leaves Raised Height (30mm Lift) Medium Duty Up to 80Kg Constant Load	2	<b>L43-162-R</b>	
<b>SHOCK ABSORBER</b>					<b>SHACKLE BUSH KIT</b>				
** Batch Number 10250 on only, Spring Seat must not be lower than 215mm									
	Twin Tube Gas Heavy Duty	2	<b>GS43-800</b>			Kit Contains: 2 x PB43-1550 4 x PB43-1551 4 x PB43-1528	1	<b>PB43-1109K</b>	
	Internal Monotube Adjustable Spring Seat Heavy Duty Spring Seat Height X = 215mm / 8.45" **	2	<b>IMS43-50800</b>		<b>U-BOLT KIT</b>				
X - Centre of Eye to Spring Seat									
	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Spring Seat Height X = 215mm / 8.45" **	2	<b>MR43-50800</b>			Suits <b>L43-162-R</b> Kit Contains: 2 x UB59-453-2	2	<b>UB59-453-2K</b>	
X - Centre of Eye to Spring Seat						Suits <b>L43-163-R</b> Kit Contains: 2 x UB59-453-2	2	<b>UB59-453-2K</b>	
<b>STRUT CAP</b>						Suits <b>L43-164-R</b> Kit Contains: 2 x UB59-437	2	<b>UB59-437K</b>	
	Strut Top Cap	2	<b>SC43-005</b>			Suits <b>L43-165-R</b> Kit Contains: 2 x UB59-437	2	<b>UB59-437K</b>	
<b>TOP OUT STOP KIT</b>					<b>SHOCK ABSORBER</b>				
Top Out Stop Kit					1	<b>WA43-539K</b>			
Recommended To Fit This Kit With All Suspension Kits To Maintain Droop Travel									
<b>BUMP STOP</b>					<b>SHACKLE</b>				
Replacement Bump Stop Adjustable 0-30mm Extension					2	<b>BS59-560</b>			
									
					Greasable: Fit in Pairs				
					2	<b>SK43-063</b>			
					<b>PIN</b>				
									
					Greasable: Fit in Pairs				
					2	<b>SP59-060</b>			
					<b>TAILSHAFT SPACER</b>				
					When Fitting Raised Suspension a Tailshaft Spacer is Required to Align the Centre Bearing and Prolong Life in Models with a 2 Piece Tailshaft				
					1	<b>S43-001</b>			