



















TYPE: Hilux
MODEL: Vigo - KUN/GGN 25/26, KZN 35/36
YEAR: 2005 to Mid 2015
DETAIL: 4x4 Single Cab, Extra Cab, Dual Cab,
 75mm (3" Lift)



FRONT		QTY	PART NUMBER	PRICE
COIL SPRING				
	Linear Rate Raised Height (3" Lift)	1	C59-354	B
	Linear Rate Raised Height (3" Lift) 80-100Kg	1	C59-318	B
SHOCK ABSORBER				
	Internal Monotube Adjustable Spring Seat Heavy Duty Original Setting of X = 226mm / 8.9"	2	IMS59-50220C	
X - Centre of Eye to Spring Seat				
	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 226mm / 8.9"	2	MR59-50220C	
X - Centre of Eye to Spring Seat Please Note That the Diff Drop Kit DD59-527K Must be Fitted When Using The Shock Absorber MR59-50220				
SHOCK ABSORBER BRACKET				
	Recommended For Optimal Remote Reservoir Positioning And Fitment	1	RM59-004	
Only For Use With MR59-50220				
STRUT CAP				
	Strut Top Cap	2	SC59-001	
DIFF DROP				
	Diff Drop Kit	1	DD59-527K	
Must Fit When Using Long Travel Shock Absorbers IMS59-50220C & MR59-50220C To Prevent C.V. Bind				
SWAY BAR RELOCATION				
	Sway Bar Relocation Kit	1	SE59-524K	
UPPER CONTROL ARM KIT				
	(Pair) 3° Castor Built In Rubber Bushes with Ball Joint	1	UCA59-003K	
Must Fit When Raising Vehicle Above 50mm To Allow For Improved Caster Angle Alignment				
BUMP STOP				
	Replacement Bump Stop Progressive Adjustable 0-30mm Extension	2	BS59-560	
Replaces Original Bump Stop. If Exceeding Listed Spring Seat Heights This MUST Be Used To Prevent Coil Bind.				
OUTER C.V. BOOTS				
	High Clearance Outer C.V. Boot Kit	1	CV59-554K	
Must Be Fitted For Lifts Over 50mm To Reduce C.V. Boot Wear. Can Also Be Used As Genuine Replacement				

REAR		QTY	PART NUMBER	PRICE
LEAF SPRING				
It is a Requirement that the Brake Adjuster BA59-002 be Fitted When Using These Leaf Springs				
	3 + 1 Leaves Raised Height (50mm Lift) Medium Duty Up to 100Kg Constant Load	2	L59-047-RP	
L59-047-RP Lifts Only 50mm to Provide a More Level Look				
	3 + 1 Leaves Raised Height (75mm Lift) Medium Duty Up to 100Kg Constant Load	2	L59-049-RP	
SHACKLE BUSH KIT				
	Kit Contains: 4 x PB59-1501 4 x PB59-1502 2 x PB59-1503	1	PB59-1094K	
U-BOLT KIT				
	Kit Contains: 2 x UB59-437	2	UB59-437K	
SHOCK ABSORBER				
	Twin Tube Gas Heavy Duty (Big Bore)	2	GS59-651	
	Internal Monotube Heavy Duty	2	IMS59-50649	
	Monotube Remote Reservoir Heavy Duty	2	MR59-50649	
BRAKE ADJUSTER				
	Recommended when Raising Vehicle	1	BA59-002	
Not required for vehicles with ABS Brake System				
SHACKLE				
	Greasable: Fit in Pairs	2	SK59-053	
PIN				
	Greasable: Fit in Pairs	2	SP59-060	
WARNING - 75MM (3") OR HIGHER LIFT				
The suspension components listed on this page are for off-road use only.				
	- Refer to Local Laws before Fitting to Registered/Road Vehicles - An Engineering Certificate may be required - Handling Characteristics will Diminish on Lifts Above 50mm (2")			
The following modifications (but not limited to) need to be made to the vehicle before the kit is fitted.				
	- Adjustable Panhard Rods - Modified Leading/Trailing Arms - Brake Hoses - Extended Bump Stops	- Gear Box & Drive Line Modifications - Steering Arms - Swaybar Modification		
Dobinsons Spring & Suspension do not accept any responsibility for injury caused to person or property through the use of the products listed on this page.				
These products do not come with any warranty or guarantee.				