



**TYPE:** Hilux  
**MODEL:** Revo - KUN/GGN/GUN 125, KUN/GUN 126, GUN13  
**YEAR:** 2015 on  
**DETAIL:** 4x4,  
 75mm Lift (3")



## FRONT

QTY

PART NUMBER

PRICE

## COIL SPRING

## Single Cab



Linear Rate  
 Raised Height (75mm Lift)  
 50-100Kg

1

C59-350

B

## Dual Cab



Linear Rate  
 Raised Height (75mm Lift)  
 Heavy Duty  
 No Accessories

1

C59-354

B



Linear Rate  
 Raised Height (75mm Lift)  
 Heavy Duty  
 30-50Kg

1

C59-318

B



Linear Rate  
 Raised Height (75mm Lift)  
 60-100Kg

1

C59-764

B

## SHOCK ABSORBER

Must Fit Diff Drop Kit, Upper Control Arm & C.V. Boot Kit When Fitting a 3" Lift.



Internal Monotube  
 Adjustable Spring Seat  
 Heavy Duty  
 Original Setting of  
 X = 233mm / 8.9"

2

IMS59-50220B

X - Centre of Eye to Spring Seat



Monotube Remote Reservoir  
 Adjustable Spring Seat  
 Heavy Duty  
 Original Setting of  
 X = 233mm / 8.9"

2

MR59-50220B

X - Centre of Eye to Spring Seat

## SHOCK ABSORBER BRACKET

Recommended For Optimal Remote  
 Reservoir Positioning And Fitment

1

RM59-004

Only For Use With MR59-50220B

## DIFF DROP

Diff Drop Kit

1

DD59-527K

Must Fit When Using Long Travel Shock Absorbers  
 IMS59-50220B & MR59-50220B To Prevent C.V. Bind

## UPPER CONTROL ARM KIT

(Pair) 3° Castor Built In  
 Rubber Bushes  
 with Ball Joint

1

UCA59-003K

Must Fit When Raising Vehicle Above 50mm To Allow For Improved Caster  
 Angle Alignment

## OUTER C.V. BOOTS

High Clearance Outer C.V. Boot Kit

1

CV59-554K

Must Be Fitted For Lifts Over 50mm To Reduce C.V. Boot Wear.  
 Can Also Be Used As Genuine Replacement

## STRUT CAP



Strut Top Cap

2

SC59-001

## BUMP STOP

Replacement Bump Stop  
 Progressive Adjustable 0-30mm Extension

2

BS59-560

Replaces Original Bump Stop.  
 If Exceeding Listed Spring Seat Heights This MUST Be Used To  
 Prevent Coil Bind.

## REAR

QTY

PART NUMBER

PRICE

## LEAF SPRING



2 + 1 Leaves **Parabolic**  
 Raised Height (50mm Lift)  
 Medium Duty  
 Up to 60Kg Constant Load

2

L59-178-RP

L59-178-RP Lifts Only 50mm to Provide a More Level Look



2 + 1 Leaves **Parabolic**  
 Raised Height (75mm Lift)  
 Heavy Duty  
 Up to 60Kg Constant Load

2

L59-179-RP

## SHOCK ABSORBER



Twin Tube Gas  
 Heavy Duty

2

GS59-229



Internal Monotube  
 Heavy Duty

2

IMS59-50229



Monotube Remote Reservoir  
 Heavy Duty

2

MR59-50229

## U-BOLT KIT



Kit Contains:  
 2 x UB59-437

2

UB59-437K

## SHACKLE



Rear of Rear Spring

2

SK59-064

## SHACKLE BUSH KIT



Kit Contains:  
 2 x PB59-1503  
 4 x PB59-1501  
 4 x PB59-1502

1

PB59-1094K

## PIN



Front of Rear Spring  
 Greasable: Fit in Pairs

2

SP59-060

This Part Is Recommended With All Kits As The Fuel Tank Location Inhibits  
 Original Bolt Removal.

## TAILSHAFT SPRACER KIT

Tailshaft Centre Bearing Spacer Kit Helps  
 To Reduce Driveline Vibration In Lifted  
 Vehicles.

Should Be Fitted To All Lifted Vehicles.  
 Lowers The Centre Bearing 12 or 24mm.

1

WA59-553K

## WARNING - 75MM (3") OR HIGHER LIFT

The suspension components listed on this page are for off-road use only.



- Refer to Local Laws before Fitting to Registered/Road Vehicles
- An Engineering Certificate may be required
- Handling Characteristics will Diminish on Lifts Above 50mm (2")

The following modifications (but not limited to) need to be made to the  
 vehicle before the kit is fitted.



- Adjustable Panhard Rods
- Modified Leading/Trailing Arms
- Brake Hoses
- Extended Bump Stops
- Gear Box & Drive Line Modifications
- Steering Arms
- Swaybar Modification

**Dobinsons Spring & Suspension do not accept any responsibility  
 for injury caused to person or property through the use of the  
 products listed on this page.**

These products do not come with any warranty or guarantee.